

NC40 UC

PRENSADORA | CRIMPING

FINN-POWER
Crimping since 1973



NC40 UC nut crimping machines produce accurate and consistent results when crimping the nuts, ferrules and bushings on ends of hydraulic hoses. Their various serviceable features make them suitable for serial production.



Crimping Range: 12 - 105mm



93 tons of crimping force



Hose size up to 2"

TECHNICAL SPECS

DESCRIPTION	NC40 UC
Hose size	2"
Crimping range \varnothing (mm)	12-105
Die type ¹	NC20/30/40
Max opening ² (mm)	+26
Master die shoe length (mm)	37
Motor (kW)	3
Crimping force (kN)	930
Number of crimps/hour ³	2100
Dimensions	
width (mm)	885
length (mm)	835
height (mm)	997
Weight (kg)	240

1. See table for standard die set data

2. This tabular value must be added to min.crimping dia of die set

3. Theoretical with 1/2" hose \varnothing 10 mm

4. NC20 and NC30 dies can be used with adapter dies

*Subject to change without prior notice

STANDARD DIE SETS*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
703955/63	63.0 - 69.0	5
703955/69	69.0 - 73.0	5
703955/73	73.0 - 81.0	6
703955/81	81.0 - 93.0	7
703955/93	93.0 - 96.0	7

*In addition to the standard die sets, a wide range of special die sets for different diameters, lengths and forms is available

OPCIONAL EXTRAS



LONG LIFE
Auto greasing system



EASY HANDLING
Remote control unit

UC CONTROL



UC1

Pressure crimping



UC2

Multi-step crimping



UC3

Data report