



Finn-Power P20 CS is an ideal choice for service vehicles. This reliable Finn-Power crimping machine is perfect when a variety of sizes and types of fittings need to be crimped in.

This machine produces very efficient and accurate crimping results.



Crimping Range: 10 - 61mm



137 tons of crimping force



Hose size up to 1 1/2"

TECHNICAL SPECS

DESCRIPTION	P20CS
Hose size	1 1/2"
Die type ¹	20
Crimping range Ø (mm)	10-61
Max opening ² (mm)	+25
Master die shoe length (mm)	80
Controls	2 buttons
Motor (kW) ³	1.5
Voltage (V) ⁴	12
Max pressure (bar)	275
Crimping force (kN)	1370
Number of crimpings/hour ⁵	250
Size	
width (mm)	533
length (mm)	571
height (mm)	387
Weight inclu oil (kg)	83

STANDARD DIE SETS*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)	CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
20-10	10.0 - 12.0	55	20-27	27.0 - 31.0	70
20-12	12.0 - 14.0	55	20-31	31.0 - 36.0	70
20-14	14.0 - 16.0	55	20-36	36.0 - 41.0	75
20-16	16.0 - 19.0	55	20-41	41.0 - 47.0	75
20-19	19.0 - 23.0	55	20-47	47.0 - 54.0	85
20-23	23.0 - 27.0	55	20-54	54.0 - 61.0	85

1. See table for standard die set data
2. This tabular value must be added to min. crimping dia. of die set
3. Overload controlled
4. Optional 24 V supply voltage
5. Theoretical with 1/2" hose Ø 10 mm

* In addition to the standard dies, a wide range of special die sets for different diameter, length and form is available.

OPCIONAL EXTRAS



CONVENIENCE
Adjustable control unit



SPEED
Quick change and QC Tool base



EASY POSITIONING
Mechanical back stop device