



Finn-Power P20X and P32X crimping machines are cost-effective alternatives for single-piece production.

With the same significant advantages than the other Finn-Power P-models (precision, durability, force and ease of use), P20X and P32X-models are totally unmatched in their own class.



Crimping Range: 10 - 61mm



137 tons of crimping force



Hose size up to 1 1/2"

## TECHNICAL SPECS

DESCRIPTION	P20X
Hose size	1 1/2"
Crimping range (mm)	10-61
Die type <sup>1</sup>	20
Max opening (mm) <sup>2</sup>	+25
Master die shoe length (mm)	80
Motor (kW) <sup>3</sup>	2.2
Standard voltages (V) <sup>4,5</sup>	230 or 400
Crimping force (kN)	1370
Noise level (dB(A))	71
Protection class	IP54
Overall dimensions:	
length (mm)	525
width (mm)	515
height (mm)	564
Weight without oil (kg)	110

## STANDARD DIE SETS\*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)	CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
20-10	10.0 - 12.0	55	20-27	27.0 - 31.0	70
20-12	12.0 - 14.0	55	20-31	31.0 - 36.0	70
20-14	14.0 - 16.0	55	20-36	36.0 - 41.0	75
20-16	16.0 - 19.0	55	20-41	41.0 - 47.0	75
20-19	19.0 - 23.0	55	20-47	47.0 - 54.0	85
20-23	23.0 - 27.0	55	20-54	54.0 - 61.0	85

1. See table for standard die set data

2. This tabular value must be added to min.crimping dia. of die set

3. 1-phase 1.5 kW

4. 1-phase 100 or 230 V

5. Other voltages upon request

\* In addition to the standard dies, a wide range of special die sets for different diameter, length and form is available.

## OPCIONAL EXTRAS



### SPACE SAVING

Die set rack



### SPEED

Quick change and QC Tool base



### EASY POSITIONING

Mechanical back stop device