



Finn-Power P32 CS is an ideal choice for service vehicles. This reliable Finn-Power crimping machine is perfect when a variety of sizes and types of fittings need to be crimped in.

This machine produces very efficient and accurate crimping results.



Crimping Range: 10 - 87mm



200 tons of crimping force



Hose size up to 2"

## TECHNICAL SPECS

DESCRIPTION	P32CS
Hose size	2"
Die type <sup>1</sup>	32
Crimping range $\varnothing$ (mm)	10-87
Max opening <sup>2</sup> (mm)	+33
Master die shoe length (mm)	80
Controls	2 buttons
Motor (kW) <sup>3</sup>	1.5
Voltage (V) <sup>4</sup>	12
Max pressure (bar)	275
Crimping force (kN)	2000
Number of crimpings/hour <sup>5</sup>	150
Size	
width (mm)	543
length (mm)	626
height (mm)	421
Weight inclu oil (kg)	116

## STANDARD DIE SETS\*

CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)	CODE	CRIMPING DIAMETER (MM)	LENGTH (MM)
32-10	10.0 - 12.0	55	32-34	34.0 - 39.0	75
32-12	12.0 - 14.0	55	32-39	39.0 - 45.0	75
32-14	14.0 - 16.0	55	32-45	45.0 - 51.0	90
32-16	16.0 - 19.0	55	32-51	51.0 - 57.0	90
32-19	19.0 - 22.0	55	32-57	57.0 - 63.0	100
32-22	22.0 - 26.0	70	32-63	63.0 - 69.0	110
32-26	26.0 - 30.0	70	32-69	69.0 - 74.0	110
32-30	30.0 - 34.0	70	32-74	74.0 - 78.0	110
			32-78	78.0 - 87.0	110

1. See table for standard die set data
2. This tabular value must be added to min. crimping dia. of die set
3. Overload controlled
4. Optional 24 V supply voltage
5. Theoretical with 1/2" hose  $\varnothing$  10 mm

\* In addition to the standard dies, a wide range of special die sets for different diameter, length and form is available.